


SURFACE MOUNT CRYSTAL OSCILLATOR FCXO-06



Actual size

Specifications

Item	Standard specifications		
Frequency range(MHz)	1.0 to 80.0		
Frequency tolerance (ppm)(at 25°C)	10, ±20, ±30, ±50, ±100		
V _{DD} sensitivity(ppm)	±1.0		
Storage temperature range(°C)	-40 to +85		
Operating temperature range(°C)	-10 to +60	-20 to +70	-40 to +85
Frequency versus temperature characteristics(ppm) (Refer to 25°C)	±15	±20	±30
	30	30	50
	±50	±50	±100
Supply voltage(V)	1.60 to 3.63		
Current consumption (mA)	5(Typ.)/20MHz@3V, 8(Typ.)/50MHz@3V (Depends on frequency and supply voltage)		
Output level(V)	CMOS @1.8 to 3.3		
	TTL @3.3		
Symmetry(%)	50 10, 50 ±5		

"Stand-by" CTRL table

Stand-by	Output
"H"	Output enabled.
"L"	Oscillation stop and High impedance output.

Bypass capacitor should be connected between V_{DD} and GND due to the stabilized operation for the crystal oscillator.


- Please consult us for customized specifications.
- All specifications and markings subjected to change without notice.

Features

- Compact design (2.0mm × 1.6mm × 0.8mm Max., Weight : 8.6mg).
- Wide range of operating supply voltage:1.60 to 3.63V
- Ceramic package and metal lid assures extreme accuracy and high reliability by electron beam sealing. Lead-free soldering is available.
- Applications Laptop PC, DSC, DVC, W-LAN


Dimensions

Unit : mm



Taping

Unit : mm



RIVER RIVER ELETEC CORPORATION
URL <http://www.river-ele.co.jp>

Head Office 2-1-1 Fujimigaoka Nirasaki Yamanashi Japan
Phone 81-551-22-1211 Fax 81-551-22-6645
Tokyo Office 4-40-14 Nishishinjuku Shinjuku-ku Tokyo Japan
Phone 81-3-3377-5444 Fax 81-3-3374-2865
Osaka Office Phone 81-6-6998-4888 Fax 81-6-6998-4899

River Electronics(Singapore)Pte.Ltd Phone 65-6258-7874 Fax 65-6258-7366
Taiwan River Co.,Ltd. Phone 886-2-8988-2811 Fax 886-2-2983-4785
Xi'an River Electronics Corporation Phone 86-29-88697274 Fax 86-29-88635134